



1. ZIP SYSTEM® SHEATHING*.
 2. CODE APPROVED WEEP SCREED.
 3. TAPE THE TOP EDGE OF FLASHING WITH ZIP SYSTEM™ TAPE OR ADHESIVE BACKED FLASHING MEETING AAMA 711 OR AC148.
 4. ZIP SYSTEM ROLLER. ROLL ALL TAPE.
 5. DRAINAGE MEDIUM (MINIMUM 1/8-INCH THICK).
 6. ONE LAYER OR WATER-RESISTIVE BARRIER WITH A PERFORMANCE AT LEAST EQUIVALENT TO GRADE D BUILDING PAPER.
 7. VERTICAL AND HORIZONTAL CONTROL JOINTS AS NEEDED, DESIGNER OF RECORD TO SPECIFY TYPE AND LOCATIONS).
 8. METAL LATH.
 9. TRADITIONAL HARD-COAT STUCCO INSTALLED IN ACCORDANCE WITH THE MANUFACTURER'S OR THE PORTLAND CEMENT ASSOCIATION (PCA) RECOMMENDATIONS WITH THE MOST RESTRICTIVE CONTROLLING.
- * ZIP SYSTEM SHEATHING IS APPROVED TO REPLACE THE FIRST LAYER OF A TWO LAYER WATER RESISTIVE BARRIER SYSTEM.

NTS

07-12-2018
ZIP SYSTEM® SHEATHING AND HARD COAT STUCCO AT CRAWL SPACE - OPTION B

H-2

Questions? Call us at 800.933.9220 ext. 2716 or visit our website at zipsystem.com



These construction details are provided to assist in the installation of ZIP System® product(s) and may not apply to every situation. Manufacturer accepts no responsibility or liability for the use of these or other construction details.