

AdvanTech® Subflooring Specifications (4' x 8' sheet) ¹					
Mill	Panel Thickness (inches)	Approximate Weight per Panel	Panels per Unit	Edge Profile	Span Rating
Easton, ME	19/32	64 lbs.	55 pcs.	T&G	20 oc
	23/32	72 lbs.	45 pcs.		24 oc
Commerce, GA	23/32	76 lbs.	45 pcs.	T&G	24 oc
Crystal Hill, VA	19/32	68 lbs.	55 pcs.	T&G	20 oc
	23/32	78 lbs.	45 pcs.		24 oc
	1	110 lbs.	35 pcs.		32 oc
	1-1/8	120 lbs.	30 pcs.		48 oc
Spring City, TN	23/32	86 lbs.	45 pcs.	T&G	24 oc
Broken Bow, OK	23/32	85 lbs.	45 pcs.	T&G	24 oc
	7/8	103 lbs.	40 pcs.		32 oc
	1-1/8	123 lbs.	30 pcs.		48 oc

AdvanTech® Sheathing Specifications (4' x 8' sheet) ^{1, 2}					
Mill	Panel Thickness (inches)	Approximate Weight per Panel	Panels per Unit	Edge Profile	Span Rating
Easton, ME Commerce, GA Broken Bow, OK	1/2	55 lbs.	70 pcs.	SE, T&G ³	32/16 oc
	5/8	66 lbs.	55 pcs.		40/20 oc
Crystal Hill, VA	1/2	55 lbs.	70 pcs.	SE, T&G ³	32/16 oc
	5/8	70 lbs.	55 pcs.		40/20 oc
	23/32	78 lbs.	45 pcs.		48/24 oc
Broken Bow, OK	1/2	57 lbs.	70 pcs.	SE, T&G ³	32/16 oc
	5/8	73 lbs.	55 pcs.		40/20 oc

¹ Net face width is 47 1/2" on tongue and groove panels

² All AdvanTech sheathing carries a Structural 1 rating

³ T&G AdvanTech sheathing is only available in the 5/8-inch panel