



August 17, 2021

Ben Richardson
Huber Engineered Woods
10925 David Taylor Dr #300
Charlotte, NC 28262

RE: Huber EXACOR™ testing with Bostik adhesives

Dear Mr. Vegas,

Thank you for your interest in Bostik products. We have received samples of the Submitted Materials listed below from you along with your request that we test for adhesion to the Submitted Materials. We have performed a standard adhesion test, ASTM D1002 and/or ANSI shears, in Bostik's Technical Service Laboratory, and based on the results I am pleased to inform you that each of the Bostik Products listed below adhered well to the surface of the Submitted Materials when applied in accordance with instructions and guidelines referenced in the next paragraph

Submitted Material

- Huber Engineered Woods – EXACOR™

Bostik Products:

- **Resilient/soft flooring adhesives**

LOCK A699 PSA	HydraStix 95 Transitional
LOCK A499 PSA	HydraStix 95 Broadloom
LOCK A195 VCT	HydraStix 95 Resilient
LOCK A490 LVT	Stix 5900
Wood Tack	Stix 2199
LOCK A495 AERO	Stix 2230
	Stix 6010
	Stix 5300
	GoldStix

- **Hardwood adhesives**

Pro-MSP	Pro-Cure
GreenForce	EFA+
Ultra-Set SingleStep 2	BEST

Bostik, Inc.
11320 W. Watertown Plank Road, Wauwatosa, WI 53226-3413 USA, Phone: +1|414|774|2250 - Fax: +1|414|774|8075
www.bostik.com



Page 2

Wauwatosa, August 17, 2021

- **Tile & Stone installation**
GoldPlus
BlackTop
UltraSet Advanced
All Bostik (118.1, 118.4, 118.11 and 118.15) mortars

- **Surface Preparation**
Webcrete 95 Grey Patch
Webcrete 98 PrepStar
UltraFinish Pro RampStar

Customers using the Bostik Products should follow (i) all instructions and guidelines, including but not limited to trowel recommendations, in the most recent Technical Data Sheet and any other instructions, guidelines, and data published by Bostik regarding the Bostik Product being used, (ii) the flooring and panel manufacturer's instructions, guidelines, and data, (iii) applicable building codes, and (iv) standard industry guidelines in effect at the time of the installation.

Bostik will warrant the Bostik Products in accordance with Bostik's standard limited warranty for those products, including the conditions stated in that warranty, which include but are not limited to a condition placing responsibility for determining suitability for use on the buyer. Bostik's standard limited warranty can be found at <http://www.bostik.com>. ALL OTHER WARRANTIES, INCLUDING BUT NOT LIMITED TO THE WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE DISCLAIMED. Adhesion results may vary depending on jobsite conditions such as humidity and temperature.

If you have any questions, please feel free to contact me directly at 414-607-1366, or you may email me at chad.bulen@bostik.com.

Sincerely,

A handwritten signature in black ink that reads "Chad Bulen". The signature is written in a cursive, flowing style.

Chad Bulen
Bostik, Inc.
Technical Service Director
Consumer & Construction Business Unit