


PerformMAX[®] engineered wood products are manufactured to be stronger and more dimensionally stable than plywood. Utilizing advanced resin technology to create a water resistant panel, PerformMAX lies flatter with incredible stiffness. Perfect for meeting your shed floor expectations.



Available in a 19/32 and 23/32 panel thickness.

Call your Huber Engineered Woods sales representative for custom sizes.

- Advanced, moisture-resistant resin technology minimizes linear expansion, thickness swell, and warping
- Exceptional strength and stiffness for a flatter, more stable flooring
- Durable, thermally fused overlay engineered against delamination when subjected to moisture or mechanical pressure
- Textured, skid resistant surface
- Free from harmful formaldehyde or other emissions
- Unique T&G profile that virtually removes the gap normally associated with traditional T&G panels
- 25 Year Industrial Limited Warranty* *Limitations and restrictions apply. Visit HuberWood.com for details.



10925 David Taylor Drive, Suite 300 | Charlotte, NC 28262 | 800.933.8220 | HuberWood.com

The PerforMAX panel is covered by US Patent No. 6,737,155. © 2017-2018 Huber Engineered Woods LLC. PerformMAX and the accompanying PerformMAX logo are trademarks of Huber Engineered Woods LLC. AdvanTech and the AdvanTech logo are trademarks of Huber Engineered Woods. Huber is a trademark of J.M. Huber Corporation. HUB 81130 REV 3/18



ENGINEERED WOODS