

### ZIP System® R-Sheathing Specifications

	R-3	R-6	R-9	R-12
<b>ZIP System R-Sheathing Total Thickness (ZIP + Foam)</b>	Approx. 1-inch	Approx. 1.5-inch	Approx. 2-inch	Approx. 2.5-inch
<b>ZIP System Sheathing Thickness</b>	7/16"	7/16"	7/16"	7/16"
<b>Polyiso Foam Thickness</b>	1/2-inch	1-inch	1.5-inch	2-inch
<b>Apx. Weight per Panel</b>	57 lbs.	59 lbs.	62 lbs.	64 lbs.
<b>Apx. Weight per Unit</b>	1,824 lbs.	1,829 lbs.	1,426 lbs.	1,152 lbs.
<b>Available Panel Dimensions (feet)*</b>	4 x 8	4 x 8	4 x 8	4 x 8
<b>Panels per Unit</b>	32	31	23	18
<b>Units per Truck</b>	24	24	24	24
<b>Maximum Unit Stack Height</b>	3	3	3	3

### ZIP System® R-Sheathing Specifications (Longer Length Panels) \*\*

	R-3 (4 x 9 / 4 x 10)	R-6 (4 x 9 / 4 x 10)	R-9 (4 x 9 / 4 x 10)	R-12 (4 x 9 / 4 x 10)
<b>Apx. Weight per Panel</b>	64 lbs. / 71 lbs.	66 lbs. / 74 lbs.	70 lbs. / 78 lbs.	72 lbs. / 80 lbs.
<b>Apx. Weight per Unit</b>	2,048 lbs. / 2,272 lbs.	2,046 lbs. / 2,294 lbs.	1,610 lbs. / 1,794 lbs.	1,296 lbs. / 1,440 lbs.
<b>Available Panel Dimensions (feet)*</b>	4 x 9 / 4 x 10	4 x 9 / 4 x 10	4 x 9 / 4 x 10	4 x 9 / 4 x 10
<b>Panels per Unit</b>	32	31	23	18
<b>Units per Truck</b>	20 / 16	20 / 16	20 / 16	20 / 16

\* Foam insulation is oversized on one 4-ft and one 8-ft. edge relative to the ZIP Sheathing to accommodate proper gapping of panels. Panels should be installed with foam edges touching. Please coordinate panel field placement and orientation in order to take advantage of this gapping feature.

\*\* Longer length ZIP System R-sheathing panels have the same: total thickness (ZIP System sheathing and foam thickness), panels per unit, and maximum unit stack height.