

FACT SHEET: ADVANTECH™ SUBFLOOR ADHESIVE

AdvanTech™ subfloor adhesive is a foam-to-gel polyurethane adhesive that provides a strong panel-to-joist connection between framing and AdvanTech® subflooring, traditional OSB or plywood subflooring. The powerful bond helps prevent movement between the floor panels and the joists/trusses, which can lead to squeaky floors. AdvanTech subfloor adhesive is so strong it even adheres to wet and frozen lumber.

Product benefits of AdvanTech subfloor adhesive include:

- A moisture-curing bond ideal for dry, frozen or wet lumber
- Bonding power 2-5 times stronger than industry standards¹
- Provides 8 times more coverage compared to traditional caulk adhesive²
- Fast easy application with gun application and 20-minute open time
- Easy-to-apply foam quickly collapses to a high-strength gel that fills gaps for even finished floors
- Backed by a 10-Year Squeak-Free Guarantee when used as part of an AdvanTech™ Subfloor Assembly³

For more information on AdvanTech subfloor adhesive, visit AdvanTechSFA.com.

###



¹Exceeds ASTM D3498 for dry, wet and frozen wood adhesion and gap filling properties.

²One 24 oz. can of AdvanTech subfloor adhesive yields approximately 400 linear feet of gel adhesive at 1/2" bead compared to application of 28 oz. cartridge adhesive application at 3/8" bead. Coverage varies based on bead size and weather conditions.

³Limitations and restrictions apply. Visit SqueakFreeGuarantee.com for details.